

SIDES

Standard
- solid

SHELVES

Standard
- stainless steel

Options
- ciam shelves selection

INTERIORS

Standard
- satin stainless-steel

Options
- RAL epoxy powder-coating
on request
- gres finish

DOORS

Standard
- ZERO doors
- triple-glazed glass
- black screen-printing

Options
- custom RAL screen-printing
- heated glass

EXTERIOR CLADDING

Standard
- powder-coated stainless-steel in
matt black finish (RAL 7021)

Options
- RAL epoxy powder-coating on
request
- stainless steel finish



IT

Temperatura Positiva

Murale refrigerato a temperatura positiva (+2/+8°C) con profondità 400mm | vasca monolitica coibentata con poliuretano ecologico e rivestita in acciaio inox | impianto a parete con refrigerazione a circolazione forzata d'aria su tutti i livelli espositivi | versione con U.C. ermetica interna o esterna | sbrinatori elettrici automatici programmati | centralina elettronica Touch | fianchi ciechi | sportelli Zero a doppia camera con serigrafia RAL 7021 | finitura interna in acciaio inox satinato | finitura esterna in acciaio verniciato a polveri RAL 7021 | mensole in acciaio satinato regolabili su asta a cremagliera | illuminazione indiretta integrata nella telaio delle porte con strip-led no spot 3000°K | vano tecnico e basamento in acciaio verniciato | piedini inox regolabili in altezza

EN

Positive temperature

Refrigerated vertical cabinet at positive temperature (+2/+8°C) with depth 400mm | monolithic tank insulated with ecological polyurethane and covered in stainless steel | refrigeration system on the back panel with fan ventilated refrigeration on all display levels | version with built-in or remote hermetic condensing unit | programmed automatic electric defrosting | touch control panel | solid sides | double-glazed Zero doors with RAL 7021 screen printing | internal finish in satin stainless-steel | external finish in powder-coated steel RAL 7021 | satin stainless-steel shelves adjustable in height on racks | indirect lighting integrated on the door frame with 3000°K diffused LED | technical compartment and base in powder-coated stainless steel | s/s feet adjustable in height

FR




Température positive

Vitrine murale réfrigérée à température positive (+2/+8°C) avec une profondeur de 400 mm | cuve monolithique isolée avec du polyuréthane écologique et recouverte d'acier inoxydable | système de réfrigération dans le dossier avec circulation forcée d'air sur tous les niveaux d'exposition | version avec unité de condensation hermétique logée ou déportée | dégivrages électriques automatiques programmés | unité de contrôle tactile | côtés solides | portes du type Zero en triple verre avec sérigraphie RAL 7021 | finition intérieure en acier satin | finition extérieure en acier thermolaqué RAL 7021 | étagères en acier satin réglables en hauteur sur crémaillère | éclairage à bandeaux LED diffusant 3000 °K indirect intégré dans le cadre des portes | compartiment technique et base en acier thermolaqué | pieds en acier inox réglables en hauteur



+2/+16°C





Technical



ventilated



automatic / electric



R290 (int) | R452 (ext)



N. 4 / 30°C / U.R. 55%



2 / hermetic



230 V / 1 Ph / 50 Hz




3000°K



+2/+16°C

Data Sheet (built-in compressor)



Code (+SKIN)
Energy Label



Dimensions
mm



780x450x2200H
960x630x2490H

Weight
Kg



130
30

Max Pwr.
Consumption
W / A

500/3,5

Avg Operating
Consumption
KW/H


0,3

Cooling
Power/Expansion
W / °C

650/-10

GAS
Type

R290 (int)
R452 (ext)



Code (+SKIN)
Energy Label



Dimensions
mm



1480x450x2200H
1660x630x2490H

Weight
Kg



230
52

Max Pwr.
Consumption
W / A

800/5,8

Avg Operating
Consumption
KW/H


0,55

Cooling
Power/Expansion
W / °C

1150/-10

GAS
Type

R290 (int)
R452 (ext)



Code (+SKIN)
Energy Label



Dimensions
mm



2180x450x2200H
2360x630x2490H

Weight
Kg



300
74

Max Pwr.
Consumption
W / A

1200/6,5

Avg Operating
Consumption
KW/H


0,8

Cooling
Power/Expansion
W / °C

1500/-10

GAS
Type

R290 (int)
R452 (ext)



Code (+SKIN)
Energy Label



Dimensions
mm



2880x450x2200H
3060x630x2490H

Weight
Kg



390
96

Max Pwr.
Consumption
W / A

1400/8,9

Avg Operating
Consumption
KW/H

1,2


Cooling
Power/Expansion
W / °C

2000/-10

GAS
Type

R290 (int)
R452 (ext)

Optionals:




Standard shelf



Shelf T1 F1



Shelf TC F1




Shelf T5 GL



Shelf T5 GR




Shelf T7




Shelf T8



heated double
glazing



arrangement for
cabinet flush wall



electronic lock



interiors
customization



ciam connect



SLIDE doors